

ROTARY SWITCH SPECIFICATIONS

A.ELECTRICAL CHARACTERISTICS

1.RATING:	DC 30 V 1 A
2.CONTACT RESISTANCE:	DC 5 V 1 A or 1KHz 50m Ω
3.INSULATION RESISTANCE:	100m Ω min.at 500V DC
4.WITHSTAND VOLTAGE:	500V 50-60Hz 1 minute

B.MECHANICAL CHARACTERISTICS

1.ROTATIONAL TORQUE	1.5 \pm 0.5Kgf.cm
2.TOTAL POLES	2
3.POSITIONS	6

C.ENDURANCE CHARACTERISTICS

1.ELECTRICAL ENDURANCE	10,000 Cycles
2.MECHANICAL ENDURANCE	15,000 Cycles

Storage Conditions:

We would recommend storage or warehousing to not exceed 6 months after receipt of shipment. Please ensure to assemble and use within this time frame. We wish to avoid the possibility these parts deviating from the original samples you have approved and that we disclaim any responsibility for any damage that might arise if you should not follow this advice.

Storage Ambience: Temperature $-15^{\circ}\text{C} \sim 45^{\circ}\text{C}$, Humidity 55% \sim 75% and that harmful chemical gases to avoid contact with the parts e.g. acids, alkali etc...